

Draeger Sauerstoffselbstretter Oxy K-50 S

Oxygen Self-Rescuer

Umluftunabhängige Chemicalsauerstoffselbstretter der neuesten Generation, die nach Kundenwünschen und der Europäischen Norm 401 entwickelt worden sind.

Hervorragend geeignet für Bereiche in denen Sauerstoffmangel oder hohe Schadstoffkonzentrationen auftreten können.

Durch den neuen Öffnungsmechanismus „Speed Flip“ ist auch für weniger trainierte oder ungeübte Personen das Anlegen des Fluchtgerätes in wenigen Sekunden durchgeführt.

Lebensdauer bis zu 10 Jahren

Untersuchung nach G26 nicht nötig



This latest generation of self-contained chemical oxygen self-rescuers was developed in response to customer requirements and in accordance with European Standard 401.

The devices are especially designed for use in areas where a shortage of oxygen or high concentrations of hazardous substances may occur.

Due to the new opening mechanism "Speed Flip" the user can easily don the escape apparatus within seconds even with a low training expense – this can be a crucial survival factor in panic situations or in dark or smoke-filled areas.

Lifetime up to 10 years

**Price per Unit
on request**



Technische Daten:

Haltezeit nach EN 401 50 Min.
Beatmung 35 Ltr./Min.

Haltezeit bei Ruhevoratmung 180 Min
Beatmung 10 Ltr./Min.

Ein-/Ausatemwiderstände 5,0 hPa

max. Temperatur der Einatemluft 55° C

Gewicht

- ungeöffnet ca. 3,0 kg
- im Einsatz ca. 1,9 kg

Abmessungen 210 x 260 x 105 mm



Trainingsset

Mehr Informationen erhalten Sie unter:
For more information please contact:

NORDSEETAUCHER GmbH, Bramkampweg 9, 22949 Ammersbek, Germany
Tel.: +49 4102 23180; Fax: +49 4102 231820; Mobile: +49 172 4300598
Internet: www.nordseetaucher.de; E-Mail: info@nordseetaucher.de

Technical Data:

Retention time as per EN 401 50 Min.
Breathing at 35 Ltr./Min.

Retention time during preliminary
Breathing at rest 180 Min
Breathing 10 Ltr./Min.

Inhalation / exhalation resistance 5,0 hPa

Temperature of inhaled air max. 55° C

Weight

- unopened ca. 3,0 kg
- in use ca. 1,9 kg

Dimensions 210 x 260 x 105 mm